

# DS-7000

Color LCD Display | Full Workflow Integration | 256-Bit Encryption Rate

Easy-to-use  
digital recording  
and editing for  
professionals.  
**Dictation Defined.**



**OLYMPUS**

Designed for professionals who rely on secure, flexible, reliable products as integral parts of their office workflow, the DS-7000 features real-time 256-bit file encryption, a redesigned, independently housed microphone, enhanced battery life and next-generation Olympus Dictation Management Systems (ODMS) software.



The power of speech: easy, mobile and secure.

## **DS-7000**

- Precise slide switch for full control in your palm
- Speech-optimized microphone
- Full integration into professional workflows possible
- Up to 200 customized dictation tags selectable

## **Enhanced security.**

Device password protection and DSS Pro real-time 128- or 256-bit file encryption makes the DS-7000 ideal for workplace environments that deal with sensitive information.

## **Endless flexibility.**

A vast array of functions and accessories, audio codes and indexing options, as well as support for multiple work types and users, makes the DS-7000 customizable enough to suit any purpose in any IT environment. The ODMS software is compatible with Microsoft Windows 7, Vista and XP and Mac OS X.

## **Superior sound and quality.**

The DS-7000's redesigned, speech-optimized microphone is independently housed for flawless sound reproduction. It offers multiple recording modes, as well as two quality levels – QP (16 kHz/28 kbps) and SP (12 kHz/13.7 kbps).

## DS-7000 | Professional Dictation



Recording format	DS2 (Digital Speech Standard Pro)
Internal memory	SD-card: 512 MB to 32 GB
External memory	SD card (SD/SDHC/SDXC) up to 64GB
Frequency reponse (internal microphone)	QP mode: 148 hours SP mode: 303 hours
Input Level	-70 dBv
PC Interface	USB
LCD	Large LCD screen with backlight
LED	Yes
Folders Messages	5 folders/200 messages per folder
Sampling Frequency	QP: 16 khz/28 kbps SP: 12 kHz/13.7 kbps
Overall Frequency Response	QP: 200 - 7,000 Hz SP: 200 - 5,000 Hz
LP Mode	Yes
Voice-activated recording	Yes
Play sync recording	Yes
Demographic Data Input	Yes
Practical Maximum Output	250 mW
Write Protection	Yes
Speaker	Built-in ø23mm round dynamic speaker
Microphone Jack	3.5mm mini-jack, 2 kΩ
Earphone Jack	3.5mm mini-jack, 8 Ω or more
Batteries	Rechargeable LI-42B : li-ion- battery (710mAh) Up to 26 hours of recording time with one battery charge
External Power Supply	No
Battery Life	Recording: (rechargeable batteries) QP mode: Approximately 30 hours SP mode: Approximately 37 hours  Playback: All modes: Approximately 35 hours
Dimensions	4.47 x 1.97 x 0.67 in. (113.5 x 50.0 x 17 mm), without protrusions
Weight	3.7 oz (105 g ), including alkaline batteries
OS Supported	Microsoft WindowsR XP: Professional / Home Edition SP3 x86 Professional / Home Edition SP2 x64 Microsoft Windows VistaR: Ultimate / Enterprise / Business / Home Premium / Home Basic SP2 (both x86/64) Microsoft Windows 7R: Ultimate / Enterprise / Professional / Home Premium (both x86/64) Ultimate / Enterprise / Professional / Home Premium SP1 (both x86/64)  Mac OS X 10.4.11 - 10.7
CPU	Windows: Microsoft WindowsR XP / Vista / 7: 1 GHz or higher  Macintosh: PowerPCR G3 500 MHz or more, or Intel Core Solo/Duo 1.5 GHz or more
RAM	Windows: Microsoft WindowsR XP: 256 MB or more Microsoft Windows VistaR: 1 GB or more Microsoft Windows 7R: 1 GB or more (32 bit) / 2 GB or more (64 bit) Macintosh: 256 MB or more (512 MB or more is recommended)
Video Card and Display	Windows: 800 x 600 pixels or more, 65,536 colors or more (16,770,000 colors or more is recommended) Macintosh: 1024 x 768 pixels or more, 32,000 colors or more
Removable Drive	CD or DVD drive
USB Port	At least one free USB port

**OLYMPUS**

[olympusamericaprodictation.com](http://olympusamericaprodictation.com)



OlympusProDictation



@ProDictation